



Product Service

CERTIFICATE

No. Z2 115676 0010 Rev. 00

Holder of Certificate: **Solar Fabrik GmbH**
Hermann-Niggemann-Str. 7-9
63846 Laufach
GERMANY

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 701262605401-00

Valid until: 2030-10-30

Date, 2026-04-10

(Zhulin Zhang)

CERTIFICATE

No. Z2 115676 0010 Rev. 00

Model(s):

Mono S4 Trend White silver S4-DGxxx-96TMax,
 xxx = 435 to 470 in steps of 5;
Mono S4 Trend White S4-DGxxx-96TMax,
 xxx = 435 to 470 in steps of 5;
Mono S4 Trend Black S4-DGxxx-96TMax,
 xxx = 435 to 470 in steps of 5;
Mono S4 Trend Full Black S4-DGxxx-96TMax,
 xxx = 435 to 470 in steps of 5;
Mono S4 Trend Full Black S4-SGxxx-96TM,
 xxx = 435 to 470 in steps of 5;
Mono S4 Trend White silver S4-DGxxx-108TMax,
 xxx = 485 to 530 in steps of 5;
Mono S4 Trend White S4-DGxxx-108TMax,
 xxx = 485 to 530 in steps of 5;
Mono S4 Trend Black S4-DGxxx-108TMax,
 xxx = 485 to 530 in steps of 5;
Mono S4 Innovation Powerline S4-DGxxx-64IVP,
 xxx = 250 to 270 in steps of 5;
Mono S4 Trend White S4-DGXXX-108T,
 xxx = 425 to 465 in steps of 5;
Mono S4 Trend White silver S4-DGXXX-108T,
 xxx = 425 to 465 in steps of 5;
Mono S4 Trend Black S4-DGXXX-108T,
 xxx = 425 to 465 in steps of 5;
Mono S4 Trend Full Black S4-DGXXX-108T,
 xxx = 425 to 465 in steps of 5;
Mono S4 Trend Project White S4-DGxxx132TPrj,
 xxx = 675 to 720 in steps of 5;
Mono S4 Trend Project White BF S4-DGxxx132TPrj,
 xxx = 675 to 720 in steps of 5;
Mono S4 Trend Project White S4-DGxxx-132TMax,
 xxx = 590 to 655 in steps of 5;
Mono S4 Trend Project White BF S4-DGxxx-132TMax,
 xxx = 590 to 655 in steps of 5;
Mono S4 Trend White silver S4-DGxxx-120T,
 xxx = 475 to 520 in steps of 5;
Mono S4 Trend White S4-DGxxx-120T,
 xxx = 475 to 520 in steps of 5;
Mono S4 Trend Black S4-DGxxx-120T,
 xxx = 475 to 520 in steps of 5;
Mono S4 Trend Full Black S4-DGxxx-120T,
 xxx = 475 to 520 in steps of 5;
Mono S4 Innovation Powerline White silver S4-DGxxx-144IVP,
 xxx = 535 to 605 in steps of 5;
Mono S4 Innovation Powerline White S4-DGxxx-144IVP,
 xxx = 535 to 605 in steps of 5;
Mono S4 Innovation Powerline Black S4-DGxxx-144IVP,
 xxx = 535 to 605 in steps of 5;
Mono S4 Innovation Powerline Full Black S4-DGxxx-144IVP,
 xxx = 535 to 605 in steps of 5;
Mono S4 Innovation Powerline White silver S4-DGxxx-156IVP,
 xxx = 590 to 660 in steps of 5;
Mono S4 Innovation Powerline White S4-DGxxx-156IVP,
 xxx = 590 to 660 in steps of 5;
Mono S4 Innovation Powerline Black S4-DGxxx-156IVP,
 xxx = 590 to 660 in steps of 5;
Mono S4 Innovation Powerline Full Black S4-DGxxx-156IVP,
 xxx = 590 to 660 in steps of 5;
 xxx is standing for rated output power at STC



CERTIFICATE

No. Z2 115676 0010 Rev. 00

Parameters:

Test Laboratory:

Zhejiang HJE Co., Ltd.
3-4/F., Building 1, No. 3556,
Linggongtang Road, Nanhu District
Jiaxing, Zhejiang, China
Framed, with Junction box,
Cable and Connectors.

Construction:

Safety Class:

Maximum System Voltage:

Fire Safety Class:

Class II
1500 V DC
Class A according to UL 790

Tested according to:

IEC 61215-1:2021
EN IEC 61215-1:2021/AC:2021
IEC 61215-1-1:2021
EN IEC 61215-1-1:2021
IEC 61215-2:2021
EN IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023